

UNITED STATES PATENT AND TRADEMARK OFFICE



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO
10/632,017	07/31/2003	Olaf Abels	71084	9343
23872 7590 02/05/2007 MCGLEW & TUTTLE, PC P.O. BOX 9227 SCARBOROUGH STATION SCARBOROUGH, NY 10510-9227		EXAMINER		
			GARCIA, ERNESTO	
			ART UNIT •	PAPER NUMBER
			3679	
		• • •	<u></u>	
·			MAIL DATE	DELIVERY MODE
		•	02/05/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.



UNITED STATES DEPARTMENT OF COMMERCE U.S. Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

10/632 012

APPLICATION NO./	FILING DATE	FIRST NAMED INVENTOR /	ATTORNEY DOCKET NO.
CONTROL NO.		PATENT IN REEXAMINATION	
10/632,017			

EXAMINER

ART UNIT PAPER

20070130

DATE MAILED:

Please find below and/or attached an Office communication concerning this application or proceeding.

Commissioner for Patents

The reply brief filed on January 11, 2007 is acknowledged.

DANIEL P. STODOLA SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 3600

ATTORNEY DOCKET NO: 71084

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant

: ABELS et al.

Serial No

: 10/632,017

Confirm. No: 9343

Filed

: July 31, 2003

For

: BALL-AND-SOCKET JOINT

Art Unit

: 3679

Examiner

: Ernesto Garcia

Dated

Noted 2/2/07

: January 11, 2007

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

REPLY BRIEF

In response to the Examiner's Answer of November 16, 2006 Applicant hereby replies.

102(b) rejection - Yao

The Examiner's Answer states that the sliding ring A1 as identified by the Examiner, which is embedded in the sealing bellows, rotates along with the sealing bellows. However, Yao fails to disclose a sliding ring that is mounted to slide in a ball race that is fixed to the ball pivot. In the present invention, the sliding ring receives the pivot-side edge of the sealing bellows (Claim 1, line 8: "a sliding ring receiving said pivot-side edge area of said sealing bellows"). The sliding ring of the present invention slides within the ball race. This is a different approach than that of Yao. In Yao, the embedded element (A1) fails to slide in the ring collar 13 since the embedded element (A1) is surrounded by the sealing bellows 8. Even

1